

---

## Electronically controlled hot air gun HG 2300 E Hot Air Tools



---

### Applications :



Removing edgeband



Shrinking cable sleeves



Welding Plastic

## **Technical Specifications :**

| <b>Technical specifications electronically controlled hot air gun HG 2300 EM</b> |   |
|--|---|
| <b>Nominal power consumption</b>   | 2300 W  |
| <b>Temperature</b>   | 50-600 掬 C                                    |
| <b>With temperature control</b>  | Yes   |
| <b>With temperature indication</b>   | No  |
| <b>Air volume</b>  | 600 l/min                                     |
| <b>Air flow control</b>  | Continuously variable                         |
| <b>Weight of machine</b>   | 0.850 kg                                      |
| <b>Length/dia. (at knock guard)</b>  | 375 mm / 100 mm                               |
| <b>Voltage</b>   | 230 V /?50 Hz (other voltages also available) |
| <b>Min. frequency</b>  | 50 Hz   |
| <b>Power consumption</b>   | 2300 W  |
| <b>Min. temperature range</b>  | 50 掬 C  |
| <b>Max. temperature range</b>  | 600 掬 C                                       |
| <b>Temperature control</b>   | Continuously variable                         |
| <b>Temperature regulation</b>  | Continuously variable                         |
| <b>Max. airflow rate</b>   | 600 l/min                                     |
| <b>Airflow regulation</b>  | Continuously variable                         |
| <b>Motor</b>   | BLDC motor                                    |
| <b>Motor life</b>  | approx. 5000 hrs.                             |
| <b>Heating element</b>   | Ceramic                                       |
| <b>Heater life</b>   | approx. 800 hrs.                              |
| <b>Delivery nozzle</b>   | 30 mm   |
| <b>Nozzles</b>   | screw-on Professional attachments             |
| <b>Mains power cord</b>  | H07RN-F 2x1                                   |
| <b>Power cord length</b>   | 2.5 m   |
| <b>Weight</b>  | 0.850 kg                                      |
| <b>Model</b>   | Folding box                                   |
| <b>Air pressure (static)</b>   | 3000 Pa                                       |
| <b>(electronically controlled)</b>   | Yes   |

## Details :

- **Power for professionals.** Hot air gun HG 2300 EM, ideal for industrial use, high-performance brushless motor, infinitely variable temperature (50 - 600° C) and continuously adjustable airflow (up to 600 l/min.), wear parts replaced with effortless e
- **The powerful HG 2300 EM hot air gun is suitable for use with screw-on nozzles from the STEINEL Professional range of hot-air accessories.**
- The HG 2300 EM is ideal for industrial use. The outlet nozzle with a diameter of 30 mm provides an airflow rate of up to 600 l/min.
- **Features:** fully electronic temperature and airflow control, a durable, high-performance brushless motor with a life of approx. 5,000 hours. Heater with a life of approx. 800 hours. Practical barrel shape for optimum stationary use. Airflow and temperature can be infinitely adjusted. The heater is easy to remove for servicing, the power cord can be changed without opening the enclosure, wear parts are replaced quickly and effortlessly.
- **Service-friendly:** The heater is easy to replace, the power cord can be changed without opening the enclosure.
- **Accessories:** the screw-on professional accessories are available for the HG 2300 EM. Leister attachments can also be used.

---

For more information :

Please visit : <https://www.youtube.com/watch?v=dBdOHAbvmeM>

---

Authorized Distributor in India : Pammvi Group of companies  
C- 501, Remi Bizcourt, 5th Floor,  
Plot No. 9, Shah Industrial Estate,  
Off Veera Desai Road, Andheri (W),  
Mumbai, Maharashtra, India

**Tel. Nos.** : +91-22-26731904  
+91-22-26731052  
+91-22-26732760  
**Fax** : +91-22-26743861  
**E-mail** : [info@pammvi.com](mailto:info@pammvi.com)  
**Website** : [www.pammvi.com](http://www.pammvi.com)

---