


## Hot Air Tools


### Electronically controlled hot air gun HG 2420 E



2 stage air flow



Adjustable temp.



Soft grip handle



Fine dust filter



Replaceable power cord



Suitable screw on nozzle

## Applications :



Fitting  
artificial  
limb



Industrial  
Heat  
shrinking



Smoothing  
Tarpaulins  
and Ground  
sheets



Welding in  
apparatus  
construction



Welding  
Plastic

---

## Technical Specification :

Technical specifications electronically controlled hot air gun HG 2420 E	
Dimensions (l x w x h)	357 x 75 x 89 mm
Voltage	220 - 230 V, 50/60 Hz
Min. frequency	50 Hz
Max. frequency	60 Hz
Power consumption	2200 W
Min. temperature range	80 掬 C
Max. temperature range	650 掬 C
Temperature regulation	Yes
Min. airflow rate	150 l/min
Max. airflow rate	400 l/min

<b>Airflow regulation</b>	2 stages
<b>Air volume</b>	400 l/min
<b>Motor</b>	Brush motor
<b>Heating element</b>	Ceramic
<b>Protection class (without earth terminal)</b>	II
<b>Thermostat</b>	No
<b>Thermal cut-out</b>	Yes
<b>Power cord length</b>	3 m
<b>Weight</b>	0.610 kg
<b>Accessories</b>	Using STEINEL Professional accessories
<b>Special features</b>	10mm round nozzle, including Cased

---

### **Details :**

- Reliability for all demands. Electronically controlled HG 2420 E hot air tool. 2200 W, infinitely variable temperature setting from 80 – 650 °C in 9 steps by thumbwheel. Airflow regulation in 2 stages from 150l/min to 400l/min. Suitable for construction site use, integrated fine dust filter. Outlet nozzle suitable for screw-on Professional nozzles.
- For professional users. The HG 2420 E electronically controlled hot air tool with infinitely variable temperature adjustment (80 650°C) and 2stage airflow (150 l/min. and 400 l/min.) is a powerful performer on any construction. Greater protection from dust and moisture, tougher design as well as a better insulated power cord to H07.
- Features: 2200watt  
Brush less motor, rated for 1,000 hours of operation. Infinitely variable temperature adjustment in 9 steps from 80 – 650 °C by thumb wheel, ergonomic handle with soft inlay for working safely. The integrated fine dust filter protects internal component in dusty environments. The outlet nozzle is suitable for fitting screw-on professional nozzles.
- Includes: supplied in a case, complete with 10 mm round nozzle. Service friendly:the power cord can be changed without opening the enclosure.
- Accessories: the comprehensive range of screw-on. STEINEL nozzles and consumables is optionally available. Also suitable for Leister nozzles.

**Accessories :**



Flat angled nozzle  
40\*2 mm



Round nozzle 5mm



ABS plastic welding  
rod

---

For more information : 

Please visit : <https://www.youtube.com/channel/UCgqi5TkrABBJDP3zjKsGBOA>

---

Authorized Distributor in India : Pammvi Group of companies  
C- 501, Remi Bizcourt, 5th Floor,  
Plot No. 9, Shah Industrial Estate,  
Off Veera Desai Road, Andheri (W)

**Tel. Nos.** : +91-22-26731904  
+91-22-26731052  
+91-22-26732760

**Fax** : +91-22-26743861

**E-mail** : [info@pammvi.com](mailto:info@pammvi.com)

**Website** : [www.pammvi.com](http://www.pammvi.com)

Mumbai Maharashtra INDIA. (+ 5.30 GMT)

Follow us :   